## With Preamp Amplitude is -87dBm

🚘 File Edit View Tools Extras ?	/ 🗄 🔲 りで 🗉	solation Setup Proc	edure upto 6GHz - Tr	ial3 ( 2.0 )			• - 🖸 X				
Start Grid Editor > Spectran V6		🕨 Spect	tran V6 Sweep Zoom								
	Center Frequency 3.500 000 GHz	₂ ≡ "	FFT Window Blackman Harris	start Frequency 3.4999995 GHz	Center Frequency 3.500000 GHz	Step Frequency 1.0 MHZ					
	Span Profiles Amp	More Stop	Capture Freq realtime Profile	End Frequency 3.500005 GHz	Span Frequency 10.000 kHz	RBW Frequency 10Hz	More				
> Spectrum											
▶ 🔜 Block	-55dBm Clear/With -70dBm X Max Huld			Maria	er 1,000,1594/a		-60.0 dBm 2				
▶ 🚯 Presets	-80d8m -			-88.0			1000.00 ms				
►	-90d8m -95d8m -100d0m			Ĭ							
	-105dBm -110dDm -115dDm										
► 🕲 View	-120d8m -125d8m -139d8m										
Cursor	-135d8m						aA				
▶ 📰 Legend	15040-	ter a la strange de la stra		And the second	and the state of the state of the state of the state of the	and and a surgery of the	and the second				
► 🖁 Ξ Trace Legend	-160dBm - -170dBm -				line and the second sec						
Type to search	-175dBm - -180dBm - 3,499,995kHz	3,499,994khtz 3,499,99	3,499,998iHz	3,499,999kHz 3,500,000kHz	3,500,001kHz 3,500,002kHz	3,500,003kHz	3,500,004kHz				
HTTP Server > Spectran V6							😆 🗘 II 🛨 🖻 🗙				
	Device Sta Last Error Secial Nur		Se	Samples/s 92.165k/0k/0k ectra Samples/s 0k/0k/ ectra/s 0k/0k/	Errors/s Total Errors USB Recoverier	0 0 0,00000					
USB Compression auto	USB Versk	n 0.4.253.F, N/A ersion C0 RX/TX / 6.0.2	US DI	IB Buffer Fill 3.13% IP Buffer Fill 0.00% unsfer Idle 91%/0%	USB Overflows DIP Overflows Clock Errorys	/s 0.00 /s 0.00					
Gain Control peak LO Harmonic base	Calibration Large Page RX Path	RX1, RX2, NF1, NF2, tr, L0, OSC	T T	USB Underflows/s 0.00 Underflows/s 0.00 Overflows/s 0.00	Fronteend Temps FPUA Temps PLL Look						
Type to search	TX Path	n/A	7	Time Offset 0.00ms Bytes/s 351/0	Board Power	USB PD 9V/3A 29.75d8 / 40.00d8 Disabled					
Spectran V6 Sweep Zoom					Ur a lans	unauna	\$0"±⊴×				
				14.10 505 01 00 0000 550	41 DOD	10 % 00110-1	20 % 🔳 🍙				
Aaronia RTSA-Suite PRO v2.1 Build 10245					61 DSP Load:		244.014				
Type here to search	0	🧠 📄 💁 .	🐶 🤹 😵	) 💶 🗣 🚾 🔚	🦰 24°C 🔨 🤹	💶 🏣 🕼 🕬	8/1/2022				

## Without preamp Amplitude is -40.7dBm

🧮 File Edit View To	ols Extras ?	IE	って	Isolation	Setup Proc	cedure upto	6GHz - T	rial3 ( 2.0	)					<b>i</b>	- 🖸 🗙
Start Grid Editor	Spectran V6				Spec		ep Zoom								
	DATA BOOST POWR	Center Frequency		Center Frequency		FFT W Blackma		Start Frequency 3.499 995 GHz		GHz	Center Frequency 3.500000 GHz		Step Frequency 1.0 MHz		
	C Rx1 Rx2 Tx	Span 1/4	Profiles	Amp Sabled	e Stop	Capture realtime	Freq Profile		Frequency	GHz	Span Frequen	00 kHz	RBW Frequency	More	
Spectrum														Reference	.e Level 2
▶ 🔜 Block		=	-20d8m C	lear/Write fax Hold iverage						Marker					
			-35dBm	tretage						3,500,000,156 -41.03dBm	Hu			POI Du 1000.	
Presets			-40d8m -45d8m											1000.	.001115
▶ 🤐 Main			-50d8m -55d8m -50d8m												۸.
▶ ⊚ View		=	-65d8m - -70d8m												
			-75d8m - -80d8m -85d8m												
Cursor		=	-90d8m - -95d8m -												aA
🕨 📰 Legend			-100dBm -105dBm -110dBm						and the second second	THINK					$\mathcal{V}_1$
► ह Trace Legend			-115dBm -			distant and a l	and all the states	A184.64.64		A	and the second second	NAL PROPERTY OF		a betreinigen ift bert	ALCONT OF STREET, SPIN
-			-125dBm -						a chiathailt		a de la calencia de l				
Type to search			3,499,995	kHz 3,499,995kH	z 3,499,9	197kHz	3,499,998kHz	3,499,99913	Hz 3,500	0,000kHz	3,500,001kHz	3,500,002kHz	3,500,003kHz	3,500,004kH	
HTTP Server Spectra	an V6								92.157k/0k/0k					🌣 🖸	"±⋴×
				levice State Running ast Error erial Number A3-x-03	000132.xxaaaaax			IQSamples/s Spectra Samples/s Spectra/s	cik/ok/ cik/ok/			Errors/s Total Errors USB Recoveries	0 0 . 0/0/0/0		
USB Compression	auto			SB Version 0.4.253 iontend Version C0 RX/ PGA Version 2.6.3 / 2	F, N/A X / 6.0.2 8.11 / 0.7			USB Buffer Fill DSP Buffer Fill Transfer Idle	3.13% 0.00% 91%/0%			USB Overflows DSP Overflows Clock Errors/s	s 0.00 s 0.00		-
Gain Control LO Harmonic	peak		î	alibration RX1, RX arge Pages No	2, NF1, NF2, tx, L0, OSC			TX USB Underflows/s TX Underflows/s	s 0.00 0.00			Frontend Temp FPGA Tempe	41.6°C 51.9°C		
Type to search	base		V 8	X Path 2300-4 X Path n/A	i10 / Disabled / -20			TX Overflows/s TX Time Offset MBytes/s	0.00 0.00ms 351/0			PLL Lock Board Power	both USB PD 9V/3A 26.75d8 / 40.00d8		
	_											GPS Sats	Disabled		
Spectran V6 Sweep Zoom	1													÷ \$	∎¥⋴×
						_									
Aaronia RTSA-Suite PRO v2.1	Build 10245					RO	C MST:	14:13:43.11:	3 01.08.2022	FPS: 60	DSP Load:		18 % CPU Sat:		<u>)*</u> 🖬 🔴
			C										on 📼 👩	2:13 P	M 22 둯